

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** TESLA lighting

**Supplier's address:** Service\_dpt, Mladoboleslavská 1108, 19700 Prague 9, CZ

**Model identifier:** GL274224-1

## Type of light source:

|                                                     |     |                                 |      |
|-----------------------------------------------------|-----|---------------------------------|------|
| Lighting technology used:                           | LED | Non-directional or directional: | NDLS |
| Light source cap-type (or other electric interface) | E27 |                                 |      |
| Mains or non-mains:                                 | MLS | Connected light source (CLS):   | Yes  |
| Colour-tuneable light source:                       | No  | Envelope:                       | -    |
| High luminance light source:                        | No  |                                 |      |
| Anti-glare shield:                                  | No  | Dimmable:                       | No   |

## Product parameters

| Parameter | Value | Parameter | Value |
|-----------|-------|-----------|-------|
|-----------|-------|-----------|-------|


### General product parameters:

|                                                                                                                                                       |        |                      |                                                                                                                                                            |                        |
|-------------------------------------------------------------------------------------------------------------------------------------------------------|--------|----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer                                                                         |        | 5                    | Energy efficiency class                                                                                                                                    | F                      |
| Useful luminous flux ( $\phi_{\text{use}}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) |        | 380 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2 400                  |
| On-mode power ( $P_{\text{on}}$ ), expressed in W                                                                                                     |        | 4,2                  | Standby power ( $P_{\text{sb}}$ ), expressed in W and rounded to the second decimal                                                                        | 0,00                   |
| Networked standby power ( $P_{\text{net}}$ ) for CLS, expressed in W and rounded to the second decimal                                                |        | 0,00                 | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set                                                         | 80                     |
| Outer dimensions without separate control gear, lighting control                                                                                      | Height | 125                  | Spectral power distribution in the range 250 nm to 800 nm, at full-load                                                                                    | See image in last page |
|                                                                                                                                                       | Width  | 125                  |                                                                                                                                                            |                        |
|                                                                                                                                                       | Depth  | 175                  |                                                                                                                                                            |                        |

|                                                                                                                         |                    |                                       |                |  |
|-------------------------------------------------------------------------------------------------------------------------|--------------------|---------------------------------------|----------------|--|
| parts and non-lighting control parts, if any (millimetre)                                                               |                    |                                       |                |  |
| Claim of equivalent power <sup>(a)</sup>                                                                                | Yes                | If yes, equivalent power (W)          | 36             |  |
|                                                                                                                         |                    | Chromaticity coordinates (x and y)    | 0,490<br>0,426 |  |
| <b>Parameters for LED and OLED light sources:</b>                                                                       |                    |                                       |                |  |
| R9 colour rendering index value                                                                                         | 2                  | Survival factor                       | 0,90           |  |
| the lumen maintenance factor                                                                                            | 0,95               |                                       |                |  |
| <b>Parameters for LED and OLED mains light sources:</b>                                                                 |                    |                                       |                |  |
| displacement factor (cos $\phi_1$ )                                                                                     | 0,72               | Colour consistency in McAdam ellipses | 5              |  |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | Yes <sup>(b)</sup> | If yes then replacement claim (W)     | 9              |  |
| Flicker metric (Pst LM)                                                                                                 | 0,4                | Stroboscopic effect metric (SVM)      | 0,1            |  |

(a) : not applicable;

(b) : not applicable;



Model placed on the Union market from 01/09/2021.



**EPREL registration number:** 767073

<https://eprel.ec.europa.eu/qr/767073>

**Supplier:** TESLA LIGHTING s.r.o. (Manufacturer)

**Website:** [www.tesla-lighting.cz](http://www.tesla-lighting.cz)

**Customer care service:**

**Name:** Service\_dpt

**Website:** [www.tesla-lighting.cz](http://www.tesla-lighting.cz)

**Email:** [servis@tesla-lighting.cz](mailto:servis@tesla-lighting.cz)

**Phone:** 00420775772717

**Address:**

Mladoboleslavská 1108  
19700 Prague 9  
Czech Republic